# Real-Time Control of Combined Sewer Networks

Mary K. Stinson • Urban Watershed Management Branch, Water Supply and Water Resources Division National Risk Management Research Laboratory, U. S. Environmental Protection Agency, Edison, New Jersey



#### WHAT IS RTC?

Real-time control (RTC) is a custom- designed management program for a specific urban sewerage system that is activated during a wet-weather event.

#### RTC FUNCTIONS

- Route flows in-line, off-line, to treatment plant, designated points
- Control flood, overflows (CSOs, SSOs), surcharge
- Maximize storage space
- Optimize treatment plant capacity
- Prevent operational problems
- Protect /restore receiving waters

#### REGULATORY SUPPORT

- U.S. EPA National CSO Control Policy's 9 Minimum Controls (meets storage requirement)
- CSO Long Term Control Plan (implementation)
- SSO control (implementation)
- Total watershed restoration and/or protection approach (implementation)

#### COST-SAVING FEATURE

- A new RTC system, hardware and software, costs from \$10 to \$40 million. (RTC in Vienna, under 🔲 📋 construction, may cost over \$30 million).
- RTC upgrades are much less expensive than new systems.
- U.S. conventional storage needs are estimated at \$10s of billions.
- For a given sewerage system, RTC system costs 50 to 75% of storage construction cost. (RTC in Quebec
- City was estimated at \$34 million against storage alone at \$44 million).
- Millions of dollars in savings come from RTC operation that maximizes storage.

#### RTC HARDWARE

- 1. Measurement devices
- Flow
- Water level
- Rainfall intensity
- Pollutant concentration
- 2. Regulators
- Pumps Movable gates
- Movable weirs
- 3. Communication
- Public dial telephone
- Dedicated lines
- 4. Controllers and
- Process Computers
- PID
- SCADA systems • Limit switch
- PLC
- Radio frequencies

## CITIES with RTC

**Europe** 

Antwerp

Barcelona

Malmo

Vienna

Zurich

Paris

Copenhagen

#### U.S.

Chicago Cincinnati Cleveland Detroit

Indianapolis Milwaukee Louisville

Philadelphia St. Paul Seattle

#### Japan Tokyo

Canada Edmonton Montreal

**Quebec City** St. Catherine


# RTC SYSTEM COMPONENTS

**Equipment - "**Hardware" **Control strategies -**"Software"

#### **Incorporation into** sewerage operation -

"Management"

(Recent advancements in the durability of "Hardware" and significant developments in the "Software" and "Management" components).



#### RTC MANAGEMENT (SOFTWARE) 1. Principal alternatives: Local Controls - many

types (better performance at single sites)

2. Global Control - supervisory or automated (always better performance than with local controls)

# INTEGRATED GLOBAL CONTROL

- Uses weather forecast in flow routing strategy prepares ahead for a flow event.
- Maximizes storage space in- and off-line.
- Eliminates in-line surcharges to prevent basement flooding or conduit damages.
- Delivers optimal loads to treatment plant(s).
- Protects receiving waters by prevention/control of untreated overflows.
- Directs unavoidable overflows to less sensitive receiving waters.
- Protects all system components from damages by preventing failures and downtime.


### **Impermeable** Surface Sewage Retention Tank Rain-runoff-process Combined Sewer Storage Tank CSO Deep Tunnel Treatment Plant

**Integrated Global Control** 

#### U.S. EPA RTC RESEARCH

- Eight completed projects: 1969 present
- Recently completed projects at:
- Seine-Saint-Denis, Paris Metro, France
- 2. Quebec City, Quebec, Canada
- Ongoing project at: Milwaukee Metropolitan Sewerage District (MMSD), Milwaukee, Wisconsin

- SEINE-SAINT-DENIS SITE • Two RTC alternatives were compared:
- ☐ 1. Supervisory Global Predictive (in use)☐
- ☐ 2. Local Reactive Control (simulated)
- Supervisory Global Predictive was





#### QUEBEC CITY STUDY

- Three RTC alternatives compared by simulation to static control:
- 1. Local Reactive Control (LRC) (Type 1)
- 2. Local Reactive Control (LRC) (Type 2)
- 3. Optimal Global Predictive (OGP)

#### **QUEBEC CITY STUDY RESULTS**

- All RTCs worked better than static control
- OGP RTC and LRC Type 2 were similar in performance and cost
- OGP RTC fulfilled all design objectives while LRC Type 2 did not





# MILWAUKEE METROPOLITAN SEWERAGE DISTRICT

- Ongoing U.S. EPA study evaluates performance and cost effectiveness of a complex, integrated RTC system at MMSD
- Memorandum of Understanding between MMSD and U.S. EPA provides access to:
- the system itself
- 2. historical and current operational data
- 3. interaction with operating personnel
- Completion date is April, 2006